

## AVKOTE Aqua Hardwood

### Description

Base of Binder:	Water repellent coating which breaths, does not yellow
Field of Application:	natural hard and tropical wood. For exterior and interior use
Colour:	Colourless
Supply:	Spray can, spray bottle or bulk liquid

### Technical Data

Density (20°C):	Approx. 0.79 at 20°C
Active elements	Approx. 5%

### Coatings Recommendations

Preparation:	Remove all dust, loose flakes and debris from the surface. Old wood should be sprayed over without sanding or it should be sanded down to a solid non-weathered depth. Before each new application test a small section to check the compatibility of the surface with AVKOTE Aqua Hardwood
Application:	Apply a good single coat, spraying at a distance of approx. 30 cm. After approximately 10-30 minute, remove excess material from non porous surfaces with a lint free cloth, rubbing the surface until excess material is removed. Do not use at temperatures below 10°C and a wood moisture content above 16%.
Coverage:	Approximately 50 ml per metre <sup>2</sup>
Storage:	Protect from the sun's rays and temperatures over 50°C.
Disposal:	Empty cans can be disposed of with normal refuse; full and partially emptied cans require special disposal. Do not pierce or burn cans after use.

### Safety Advice

Transport:	Aerosl - UN 1950, Aerosol, Spray Bottle - NA, Bulk Liquid - NA
Classification RID/ADR:	Aerosol - Poison free, BAGT Nr 101925, Spray Bottle - NA, Bulk Liquid - NA
Flammable. Irritates the eyes, lungs and skin. Sensitisation through inhalation and skin contact possible. Use only in well ventilated areas. Do not breath spray. In the event of accident or feeling unwell consult a doctor Keep out of the reach of children. Container is pressurised. Do not burn or force open empty containers. Keep away from sources of ignition.	

This information is a standard recommendation. The application should be adapted to local standards. No liability or claim can be made from this sheet.