

MATERIAL SAFETY DATA SHEET

according to 91/155 EC

1368700

Reviewed on: 01.02.2005

Printing date: 01.02.2005


1 Identification of the substance/preparation and of the company/undertaking

- **Product details**
- **Trade name:**
ALPOMASTIC hardener 8049 NS
- **Article number:**
8049NS
- **Application of the substance / the preparation**
Coating material
- **Manufacturer/Supplier:**
AVKO Limited
Hamble Court Business Park, Hamble Lane
Hamble, Southampton, SO31 4QJ
Tel. 00 44 23 80 455 855 Fax. 00 44 23 80 456 785
- **Further information obtainable from:**
Product safety department.
- **Information in case of emergency:**
Emergency telephone: Office Hours: Environmental Protection Dept. Fire Brigade. Out of Hours: Fire Brigade

2 Composition/information on ingredients

- **Chemical characterization**
 - **Description:**
Mixture of substances listed below with nonhazardous additions.
 - **Dangerous components:**
- | CAS NO. | Description Index R-phrases | % |
|-----------|---|--------------|
| 1761-71-3 | 4,4'-methylenebis(cyclohexylamine)
EINECS: 217-168-8
C
22-34 | 1,25- 2,50 |
| 1477-55-0 | m-phenylenebis(methylamine)
EINECS: 216-032-5
C
22-34 | 5,00- 12,50 |
| 7727-43-7 | barium sulphate, natural
EINECS: 231-784-4 | 25,00- 50,00 |

3 Hazards identification

- **Hazard description:**
 Xi Irritant
- **Information concerning particular hazards for human and environment:**
R 36/38 Irritating to eyes and skin.
- **Classification system:**
The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

4 First-aid measures

- **After inhalation:**
Supply fresh air or oxygen; call for doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:**
Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. Then consult a doctor.
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:**
Do not induce vomiting; call for medical help immediately.

GB

(continued on page 2)

MATERIAL SAFETY DATA SHEET

according to 91/155 EC

1368700

Reviewed on: 01.02.2005

Printing date: 01.02.2005

PRODUCT : **ALPOMASTIC hardener 8049 NS**

(continued of page 1)

5 Fire-fighting measures

- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards caused by the substance, its products of combustion or resulting gases:**
Formation of toxic gases is possible during heating or in case of fire.
- **Protective equipment:**
Mount respiratory protective device.
Do not inhale explosion gases or combustion gases.
- **Additional information**
Cool endangered receptacles with water spray.
Collect contaminated fire fighting water separately. It must not enter the sewage system.

6 Accidental release measures

- **Person-related safety precautions:**
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
- **Measures for environmental protection:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Measures for cleaning/collecting:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

7 Handling and storage

- **Handling:**
- **Information for safe handling:**
Take note of emission threshold.
- **Information about fire - and explosion protection:**
No special measures required.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store only in the original receptacle.
- **Information about storage in one common storage facility:**
Not required.
- **Further information about storage conditions:**
Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.

8 Exposure controls/personal protection

- **Ingredients with limit values that require monitoring at the workplace:**

CAS No.	Designation of material
7727-43-7	barium sulphate, natural

OEL

Long-term value
Rev,RD

4

mg/m³

- **Additional information:**
The lists valid during the making were used as basis.
- **Personal protective equipment:**
- **General protective and hygienic measures:**
The usual precautionary measures are to be adhered to when handling chemicals.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Avoid contact with the eyes and skin.
Do not eat or drink while working.
Be sure to clean skin thoroughly after work and before breaks.
- **Respiratory protection:** Suitable respiratory protective device recommended.
- **Protection of hands:** Protective gloves Impervious gloves
- **Eye protection:** Safety glasses Tightly sealed goggles
- **Body protection:** Protective work clothing

GB

(continued on page 3)

MATERIAL SAFETY DATA SHEET
according to 91/155 EC

1368700

Reviewed on: 01.02.2005

Printing date: 01.02.2005

PRODUCT :	ALPOMASTIC hardener 8049 NS
------------------	------------------------------------

(continued of page 2)

9 Physical and chemical properties

Appearance	
Form:	Liquid
Colour:	Colourless
Odour:	Solvent-like
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	180,0 °C
Flash point:	60,0 °C
Ignition temperature:	Undetermined.
Self-igniting:	Product is not selfigniting.
Danger of explosion:	Product does not present an explosion hazard.
Density:	1,5300 g/cm3
Solubility in / Miscibility with water:	
	Not miscible or difficult to mix.
Viscosity:	
Kinematic:	at 23,00 °C 1.300,00 mPa.s
Solvent content:	
Organic solvents:	5,00 %

10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Dangerous decomposition products:**
No dangerous decomposition products known.

11 Toxicological information

- **Acute toxicity:**
- **LD/LC50 values relevant for classification:**
- 1477-55-0 m-phenylenebis(methylamine)**
Oral, LD50: 1040 *** (rat)
Inhalative, LC50/4h: 2,4 *** (rat)
- 97952-68-6 Quaternary ammonium compounds,
benzylbis(hydrogenated tallow alkyl)methyl, salts
with montmorillonite**
Oral, LD50: 5000 *** (rat)
- 7631-86-9 silicon dioxide, chemically prepared**
Oral, LD50: 10000 *** (rat)
- **Primary irritant effect:**
- on the skin:
Irritant to skin and mucous membranes.
- on the eye:
Irritating effect.
- **Sensitization:**
No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Irritant.

GB

(continued on page 4)

MATERIAL SAFETY DATA SHEET
according to 91/155 EC

Printing date: 01.02.2005

1368700
Reviewed on: 01.02.2005

PRODUCT : ALPOMASTIC hardener 8049 NS

(continued of page 3)



12 Ecological information

- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) (#): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

13 Disposal considerations

- **Product:**
- **Waste disposal key:**
55508 Paint material
waste disposal indications
special waste burn
- **European waste catalogue**
08
WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 01
wastes from MFSU and removal of paint and varnish
08 01 11
waste paint and varnish containing organic solvents or other dangerous substances
- **Waste disposal key (CH):**
1620
Painting, lacquer and adhesive wastes with organic phase (with solvents)
- **Uncleaned packaging:**
- **Recommendation:**
Disposal must be made according to official regulations.

14 Transport information

<ul style="list-style-type: none"> • Land transport ADR/RID (cross-border) 	
ADR/RID class:	3 Flammable liquids.
Danger code (Kemler):	30
UN-Number:	1263
Packaging group:	III
Hazard label	
Description of goods:	1263 PAINT RELATED MATERIAL, SPECIAL PROVISION 640E
<ul style="list-style-type: none"> • Maritime transport IMDG: 	
IMDG Class:	3
UN Number:	1263
Label	
Packaging group:	III
EMS Number:	F-E,S-E
Proper shipping name:	PAINT RELATED MATERIAL

(continued on page 5)

MATERIAL SAFETY DATA SHEET
according to 91/155 EC

Printing date: 01.02.2005

1368700
Reviewed on: 01.02.2005

PRODUCT : ALPOMASTIC hardener 8049 NS

(continued of page 4)

• **Air transport ICAO-TI and IATA-DGR:**
ICAO/IATA Class: 3
UN/ID Number: 1263
Label



Packaging group: III
Proper shipping name: PAINT RELATED MATERIAL

15 Regulatory information

- **Labelling according to EU guidelines:**
The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.
- **Code letter and hazard designation of product:**



Xi Irritant

- **Hazard-determining components of labelling:**
m-phenylenebis(methylamine)
- **Risk phrases:**
R 36/38 Irritating to eyes and skin.
- **Safety phrases:**
S 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S 37 Wear suitable gloves.
S 60 This material and its container must be disposed of as hazardous waste.
- **National regulations:**
- **Classification according to VbF:**
-
- **Waterhazard class:**
Water hazard class 1 (#): slightly hazardous for water. Self-assessment

Further information

BAGT-Number 619004
Swiss class of toxicity 4

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant R-phrases**
R 22 Harmful if swallowed.
R 34 Causes burns.
- **Department issuing MSDS:**
Environment protection department.