

A2

Automatic Dispenser



- ➡ Piston Pump
Sequential Dispensing
- ➡ Minimum Shot : 1/384Y

SANTINT • CHINA

Address: Xushui Industrial Trade
Park, Zhengzhou.
Tel: +86 371 6785 7168

SANTINT • POLAND

Address: ul. Postepu 19. mag.5
02-676 Warszawa Polska
Email: info@santint.com

SANTINT • U.S.A

Address: 2580 Corporate Place Suite
F102 Monterey Park CA 91754 USA
Tel: +1 323 780 0484

SANTINT • AUSTRALIA

Address: 2/4 Weddel Court
Laverton North Victoria
Email: info@santint.com

A2 FEATURES >>>

Tablet And New Software
Userfriendly and cost-effective



1 Nozzle Blockage Warning


Guidance for cleaning and maintenance.



2 Self-checking While Starting


3 Piston Rod Detection

Warning when the piston is not pushed down.



4 Laser Positioning

5 Patented Nozzle Sealing



**Piston Pump
Sequential Dispensing**

- Flow Rate 600ml/min
- Efficiency 222ml/min

- Minimum Shot
1/384Y(0.077ml)

- Pump Capacity 60ml
- Stirring Speed 20rpm

- Canister Size 1.8L POM
2.3L Stainless Steel (Optional)
- NO. of Canisters Up to 16

- Can Size (D X H) Max 320mmX450mm Min 80mmX100mm
- Machine Dimension (W X D X H) 710X840X1300mm
- Packing Dimension (W X D X H) 1020X880X1500mm
12 Pieces/20"Container

- Net Weight 130Kg
- Gross Weight 165Kg
- Power 100W
- Power Supply 220V/110V 50Hz/60Hz

SANTINT
WHERE INNOVATION MEETS PRECISION

A2

Technical Parameters