

# DEVILBISS SRI *HD*

## *Fine finish spray gun*

A fine finish spray gun to provide ultra sensitive fan pattern control with the comfort of a full-size spray gun.

**DEVILBISS®**



The Devilbiss SRI *HD* is the ultimate fine finish spray gun providing superb feathering control combined with the pattern range and versatility needed for top quality fine finishing including spot repairs, shading and stencilling, whilst providing excellent comfort stability, balance and delicacy of control.

### **Typical Applications in General Industry**

- Fine shading
- Retouching
- Stencilling
- Spot repair
- Reworking

### **Suitable for these materials**

- Solvents and water based paints
- Stains and varnishes
- Inks and dyes
- Lacquers.

---

A small scale fine finish spray gun with many practical uses throughout general industry, ergonomically styled for comfort

---

Choice of HVLP or Trans-Tech® Compliant air caps provide superb atomisation of both solvent and waterbased materials

---

Stainless steel fluid tips & needles

---

Balanced air valve design for lighter trigger pull and improved air flow

---

Lightweight, strong, cast aluminium gun body

---

SRI is supplied as standard with a quality screw top gravity feed cup with 125mls. capacity

---

Optional inexpensive semi-disposable cups are available.

**SRI**  
**HD**  
by **DEVILBISS®**

finishingbrands.eu



**SRI HD Compliant Trans-Tech Spray Gun**

The SRI HD gun is constructed of the very highest grade alloys and stainless steels to ensure smooth operation as well as high impact resistance.

Every single component within the SRI HD spray gun is quality controlled and machined parts are checked to exacting tolerances.

**Example of SRI HD spray gun part numbering:**

**SRIHD-TS1-08 means...**

SRIHD = SRI HD Gravity Gun / TS1 = TS1 Air cap / 08 = 0.8 fluid tip and needle.



Kit contents are spray gun c/w selected air cap and tip set up, gravity cup, pouring funnel, spanner, torx key and cleaning brushes.

SRI HD Gravity Fluid Tip/ Needle (mm) sizes and code:
0.8, 1.0, 1.2, 1.4

Air cap Number and Type	Recommended Inlet Pressure	Air Flow @ recommended inlet pressure
HS1 HVLP	2 bar (29psi)	135 l/min (5 scfm)
TS1 Trans-Tech	2 bar (29psi)	100 l/min (4 scfm)
RS1 Trans-Tech Round Spray	1 bar (15 psi)	55 l/min (2 scfm)

Specification	SRI HD Gravity
Air Connection	1/4" Universal
Gun Weight (with cup)	485g

For further technical information refer to the SRI HD Service Bulletins

**Sales and Service through our Global Network of Industrial Distributors**

Finishing Brands Locations

- Americas: **USA** ▪ **Mexico** ▪ **Brazil**
- Europe/Asia/Africa: **United Kingdom** ▪ **France** ▪ **Germany**
- Pacific Rim: **China** ▪ **Japan** ▪ **Australia**

**DeVILBISS**®

www.finishingbrands.eu

email: marketing@finishingbrands.eu

